

halFILE Database Validation

Providing data/image validation for the halFILE™ Document Manager

Version 2.2
May 25, 2005



Systems Corporation

©Copyright 2005 hal Systems Corporation, Dallas, TX. All rights reserved.
doc # hfw0031_22

halFILE is a trademark of hal Systems Corporation.

All information contained or disclosed by this document is considered confidential and proprietary by hal Systems Corporation, except for rights expressly granted by contract in writing to other parties concerning the data or information disclosed herein. All design, manufacture, use, reproduction, and sales rights are reserved by hal Systems Corporation. Under the copyright laws, neither the documentation nor the software may be copied, photocopied, reproduced, translated, or reduced to any electronic medium or machine-readable format except in the manner described in the documentation. ©Copyright 2005 by hal Systems Corporation. All rights reserved.

Table of Contents

Overview	3
Program Set up	3
Program Operation	3
SQL Where Clause.....	4
Other Notes	5

Overview

The halFILE Database Validator, HFVALIDATE.EXE, can be used to:

1. Validate coded fields in a halFILE Database.
2. Validate Subdivision blocks and lots against the Base Edit table to ensure that the blocks and lots posted to a document are valid.
3. Validate Township sections against the Base Edit table to ensure that the sections posted to a document are valid.
4. Check for missing images.

Program Set up

HFVALIDATE.EXE is installed simply by placing it into the halFILE program directory.

Program Operation

When you run the halFILE Database Validator, HFVALIDATE.EXE, the screen below is displayed. This is used to set up the validation process.

The screenshot shows the 'halFILE Database Validator' application window. The title bar includes standard Windows window controls (minimize, maximize, close). The main interface is divided into several sections:

- Application:** A dropdown menu set to 'CCL (Calhoun County, TX thru 04)' and a checked checkbox for 'Comma-delimited output'.
- Database:** A dropdown menu set to 'LR Calhoun County, TX thru 04/2' and a text field for 'Cartridge table alias' containing 'Cartridges'.
- Output File Format:** A section with two columns: 'Available Fields' and 'Output Fields'.
 - Available Fields:** A list box containing 'PRSTAT', 'PRDOC', 'PRSERV', 'PRTYPE', 'PRMNAME', 'PRFOLDER', 'PRQUEUE', 'Volume', 'Page', 'Clerk_Number', and 'Grantor'. 'Clerk_Number' is selected.
 - Output Fields:** A list box containing 'Volume', 'Page', and 'Clerk_Number'.
 - Buttons between the columns: 'Add >', 'Add All >>', '< Remove', and '<< Clear'.
- Select * from primetable where:** A text field with the instruction '(leave blank for all records or enter a valid SQL where clause)' below it.
- Validation Options:** A group box containing two checkboxes: 'Coded fields' and 'Missing images', each with an 'info' button.
- Records processed:** A label 'Records processed' followed by the value '293719'.
- Docs with bad codes:** A label 'Docs with bad codes'.
- Docs with Missing Images:** A label 'Docs with Missing Images'.
- Code Error Log:** A text field containing 'E:\Halfile\web\misscodes.txt' and a 'View' button.
- Missing Image Log:** A text field containing 'E:\Halfile\web\missings.txt' and a 'View' button.
- Buttons:** 'Load Settings', 'Save Settings', and 'Validate' buttons are located at the bottom right.

Typical processing is performed as follows:

1. Use the Application and Database drop down boxes to select database to validate.
2. Select the fields to include in the error log by highlighting a field in the Available Fields box and clicking the ADD button to add it to the Output Field box.
3. If you wish to validate a subset of the database, then enter the SQL where clause in the box provided. See the “**SQL Where Clause**” section below for some examples.
4. In the Validation Option frame, select what you wish to validate. You can perform code (and Base Edit) validation by checking the **Coded fields** box. You perform missing image validation by checking the **Missing images** box. You may perform both types of validation at the same time.
5. Designate the error log path and file names to use in the Code Error Log and Missing Image Log boxes.
6. If you wish to save these settings for this database, click the Save Settings button
7. Click the Validate button to begin the validation. The time required to complete the validation depends on the type of validation being performed (codes and/or images) and the number of records selected.
8. When the validation is complete, click the View buttons to view the error logs.

SQL Where Clause

The following lists some examples of SQL where clauses that may be used to limit the scope of the validation to a certain set of records.

To perform validation against a range of halFILE Document Numbers:
Prserv between ‘A0000001’ and ‘A0004378’

To perform validation for a date range:
File_Date between ‘01/01/2003’ and ‘12/31/2003’
(Note that “File_Date” should be the date field name.)

To perform validation for a certain Instrument_Type:
Instrument_Type = ‘MTG’
(Note that “Instrument_Type” would be the actual database field name)

To perform validation against a range of File Numbers:
File_Number between ‘200312345’ and ‘200315444’
(Note that “File_Number” would be the actual database field name)

To perform validation for a particular Book:
Book = ‘245’
(Note that “Book” would be the actual database field name)

Other Notes

1. The Comma-delimited output check box is used to designate that output files are in standard comma-delimited format. If you uncheck the box, a bracket format is used.
2. The halFILE Document Number (PRSERV) is automatically included in the output file so you do not need to select it.
3. You can use Crystal Reports to design a report from the text file.
4. The Load Settings button is used to load previously saved settings for the selected database.
5. The Cartridge table alias box is not used under normal circumstances so leave it as is (i.e. filled with “Cartridges”).